

LS9000B-42



specifications

Pump Power	110VAC / 60 Hz
Pump Airflow	16 LPM
Pump Cycle Time	10, 15, 20, 25 Minutes
Pump Type	Compressor
Pump Alarms	Visual/Audio
Mattress Dimensions	80" x 42" x 10"
Mattress Cover Material	Fluid-Resistant Nylon
Weight Capacity	1000 lbs.
Warranty	1 Year

- The Masonair™ LS9000B Bariatric Low Air Loss and Alternating Pressure Mattress is one of the most advanced systems in the Masonair™ series.
- The microprocessor sensor technology provides continuous feedback to equalize pressure and maximize patient comfort.
- The mattress consists of (20) 10" high cell-in-cell designed air bladders.
- In case of a power failure the air cells within the 10" air cell will remain inflated offering sufficient weight support for the patient.
- For the home care and long term care markets.
- Head Pillow feature.
- CPR feature allows for rapid deflation of mattress system.
- Static function can suspend the alternating mode (has auto-recovery feature).
- Visible and audible alarms with Alarm Mute feature (3 minute auto-return feature).
- CPR valve feature allows for rapid deflation.

1.	Pump Only	LS9120B	3.	Mattress Only	LS9125B-42
	Filter	LS9120B-F	4.	Mattress Cover	LS9140-42
	Filter Cover	LS9120B-FC	5.	Bladder with Air Hole	LS9000B-42CELL1
	Fuse	LS9120B-FUSE	6.	Bladder w/o Air Hole	LS9000B-42CELL
	Fuse Holder	LS9120B-FH	7.	CPR Valve, 2 port, 4/Mattress	14012
	Hook Set	LS9120B-HS	8.	Hose Clamp, Single	LS9120-HCS
	O Rings (set of 4)	LS9120B-OR			
	Mattress Connector, 1 ea	LS9120B-MC			
2.	Tubing	LS9125B-02			
	T Clip Connector	LS9125B-03			

[Diagrams](#)

[Home](#)