

## LS9500











specifications	
Pump Power	110VAC / 60 Hz
Pump Airflow	45 LPM
Pump Cycle Time	N/A
Pump Type	Compressor
Pump Alarms	Visual / Audible
Mattress Dimensions	80" x 36" x 10"
Mattress Cover Material	Fluid-Resistant Nylon
Weight Capacity	500 lbs.
Warranty	1 Year

- The Masonair™ LS9500 Turn-Style system incorporates the functions of lateral rotation and low air loss in one unit
- The user friendly high flow control unit offers 10 comfort levels, adjustable turning cycles and maximum turn angle adjustment of up to 40 degrees.
- The continuous feedback sensor technology of the control unit will equalize pressure and maximize patient comfort.
- The mattress is constructed of (20) 8" high split-air cells over a 2" foam base with (2) 10" high side air bolsters.
- The (2) side bolsters provide the patient with optimal comfort while creating a safe environment during rotation.

- The lateral rotation mode will assist in pulmonary blood flow and mucosal drainage, while the "on demand" low air loss function will provide a cool and dry surface for prevention and treatment of pressure ulcers.
- 10, 20, 30 & 60 minute adjustable turning cycles.
- ¼, ½, ¾ & full position adjustable turning positions up to 40°.
- · Lockout feature to protect patient settings.
- Auto-Firm feature for max inflation when transferring patient and has auto-recovery after 30 minutes.
- Audible and visual low pressure alarms.
- CPR deflation in 20 seconds.

1.	Pump Only	LS9520	4.	Mattress Only	LS9525
	Fuse	LS9120B-Fuse	5.	Mattress Cover	LS9540
	Fuse Holder	LS9120B-FH	6.	Bladder	LS9550-CELL
	Male Threaded CPC Pump Connector	LS9120-CPC	7.	Manifold Complete	LS9525-CM
2.	Power Cord	LS69120-01	8.	Balster Deflation Valve Plug	LS9525-BDV
3.	CPC Connector Set	LS9525-CPC	9.	Side Bolster Right	LS9525-RSB
	Female CPC Connector with Latch	LS9120-02		Side Bolster Left	LS9525-LSB

Part Photo Search

Diagrams

LS9120-02A

Female CPC Connector w/o Latch

Home