

## Vacu-Aide® Suction Machine

HCPCS: E0600



- Smaller footprint
- Lighter weight
- Quieter
- Longer lasting battery (7325P-D and 7325P-D-EXF)
- 27 LPM (free flow) typical\*\*\*

PRODUCTS	Description
7325D-D	Vacu-Aide w/o battery, w/internal filtr
7325D-D-EXF	Vacu-Aide w/o battery, w/external filtr
7325P-D	Vacu-Aide w/btty,internl filtr,carry bag
7325P-D-EXF	Vacu-Aide w/btty,externl filtr,carry bag

SPECIFICATIONS	Description
Color	Blue & Grey
Operating Humidity Range	15 - 93% non-condensing
Operating Pressure Range	770 hPa to 1060 hPa (~7500 ft to ~1400 Ft below sea level)
Operating Temperature Range	0 - 40 C (32 - 104 F)
Product Dimensions	6.9"H x 7.0"W x 7.1"D
Product Weight	7325P-D, 7325P-D-EXF: 3.8 lb. not including power supply   7325D-D, 7325D-D-EXF: 3.4 lb. not including power supply
Size	6.9"H x 7.0"W x 7.1"D
Storage/Transport Humidity Range	0 - 93% non-condensing
Storage/Transport Temperature Range	-25 - 60 C (-13 - 140F)
Vacuum Range	50 - 550 mm Hg +/- 5%***
Warranty	7325P-D and 7325P-D-EXF: Limited 2 years on unit; limited 1 year on battery   7325D-D and 7325D-D-EXF: Limited 2 years on unit
Material Composition	Formed plastic, Vacuum Gauge, PCB, Foam

ACCESSORIES	Description
22330	Canister Kit, Drive, 1/ea, EA
18600-FILTER	Hydrophobic Filter ForSuctMachine,3/bx, BX
18600-KITN	UniversalSuctionTubing&FilterKit,1/ea, EA
22330-12	Cannister Kit, Drive,12/cs, CS
610-12B	800CC DisposableSuctionCanister&Lid,12/CV, CS
610-48BP	800CCDisposableSuctionCanister&Lid,48/CV, CS
7305D-608	BACTERIA FILTER (NON-STERILE) 12EA/PKG, PK

## ACCESSORIES

## Description

7305D-612	REPLACEMENT TUBING 6-PK, PK
7305D-614	ElbowConct,Filter, 3.375" tubing, 1ea/ea, EA
7305D-619	ELBOW (DFT) 6-PK SS, PK
7305D-632	Int Fltr Disp Canstr PK48, CS
7305D-633	Int Filter Disp Canister Comp Kit Assmd, EA
7305D-633-25	Int Fltr Disp Cnstr Comp Kit Assmd Cs 25, CS
7305D-635	800ML DISP CONTR FILTER Cart. Asml,12 P, CS
SUCP TUBING 10	Suction tubing Blue tipped 10",1/EA, EA
SUCP TUBING 72	Suction Tubing 72",1/EA, EA